

COMPANY SUPPLYING GLAZED WINDOWS & DOORS:

Modplan Ltd., Imperial Building, Bridge Street, West End, Abercarn. United Kingdom. NP11 4SB

MANUFACTURER: Modplan Ltd., Imperial Building, Bridge Street, West End, Abercarn. United Kingdom. NP11 4SB

It is hereby declared that the UPVC product, VEKA MATRIX 58, VEKA MATRIX 70 CHAMFERED, VEKA 70 FULLY SCULPTURED with double glazed units (4-20-4) 28mm for the windows and doors as identified in table 1 below, is according to the provision of the European Construction Products Regulation, if the installation is conducted according to the technical conditions of the product, installation instructions, declared product application, and simultaneously when the product complies with the following standards:

EN 14351-1:2006+A1:2010 Windows and doors-Product standard, performance characteristics- Part 1: Windows and external pedestrian doorsets without resistance to fire and/or smoke leakage characteristics.

Table 1

EN14351-1 SECTION 4.**	REQUIREMENT	WINDOWS									DOORS						Notified Body /Test Schedule S2/45144 S2/45145	
		MATRIX 58			MATRIX 70 CH			70 FULLY SCULPT			MATRIX 58		MATRIX 70 CH		70 FULLY SCULPT			
		FIXED	OPENER	TILT & TURN	FIXED	OPENER	TILT & TURN	FIXED	OPENER	TILT & TURN	SINGLE DOOR GLAZED	SINGLE DOOR PANEL	SINGLE DOOR GLAZED	SINGLE DOOR PANEL	SINGLE DOOR GLAZED	SINGLE DOOR PANEL		
2	RESISTANCE TO WIND LOAD	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
3	RESISTANCE TO SNOW AND PERMANENT LOAD	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
4	FIRE CHARACTERISTICS	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
5	WEATHER TIGHT/ WATERTIGHTNESS	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
6	DANGEROUS SUBSTANCE	None															BBA S2/45144/5	
7	IMPACT RESISTANCE	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
8	LOAD BEARING SAFETY DEVICES LOAD(N)	350N									npd	npd	npd	npd	npd	npd		
	CASEMENT 12" SIDE RESTRICTOR	HINGE TESTED ON 70 FS WINDOW 665MM X 1415MM									npd	npd	npd	npd	npd	npd		
	CASEMENT 16" SIDE RESTRICTOR	HINGE TESTED ON 70 FS WINDOW 815MM X 1415MM									npd	npd	npd	npd	npd	npd		
	CASEMENT 16" TOP RESTRICTOR	HINGE TESTED ON 70 FS WINDOW 1415MM X 816MM									npd	npd	npd	npd	npd	npd		
	CASEMENT 24" TOP RESTRICTOR	HINGE TESTED ON 70 FS WINDOW 1415MM X 1315MM									npd	npd	npd	npd	npd	npd		
	TILT & TURN GEARING 3	HINGE TESTED ON 70 FS WINDOW 1218MM X 1218MM									npd	npd	npd	npd	npd	npd		
	TILT & TURN GEARING 4	HINGE TESTED ON 70 FS WINDOW 1758MM X 1758MM									npd	npd	npd	npd	npd	npd		

BBA S2/45144/5 ITT report 45165 (issue 2)
BSI
2370/7934011(DGS)

COMPANY SUPPLYING GLAZED WINDOWS & DOORS:

Modplan Ltd., Imperial Building, Bridge Street, West End, Abercarn. United Kingdom. NP11 4SB

MANUFACTURER: Modplan Ltd., Imperial Building, Bridge Street, West End, Abercarn. United Kingdom. NP11 4SB

Table 1 continued

EN14351-1 SECTION 4.**	REQUIREMENT	WINDOWS									DOORS						Notified Body /Test Schedule	
		MATRIX 58			MATRIX 70 CH			70 FULLY SCULPT			MATRIX 58		MATRIX 70 CH		70 FULLY SCULPT			
		FIXED	OPENER	TILT & TURN	FIXED	OPENER	TILT & TURN	FIXED	OPENER	TILT & TURN	SINGLE DOOR GLAZED	SINGLE DOOR PANEL	SINGLE DOOR GLAZED	SINGLE DOOR PANEL	SINGLE DOOR GLAZED	SINGLE DOOR PANEL		
9	HEIGHT & WIDTH OF DOORSETS AND FRENCH WINDOWS	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
10	EMERGENCY EXIT DEVICES ABILITY TO RELEASE	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
11	ACOUSTIC PERFORMANCE	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
12	THERMAL TRANSMITTANCE W/M2k 4/20/4 clear float outer pane, minimum 90% ARGON, warm edge spacer min thermal conductivity 1.69, Low En inner pane minimum En 0.05	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	BBA S2/45144/5
13	RADIATION PROPERTIES	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
14	AIR PERMEABILITY	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
15	DURABILITY	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
16	OPERATING FORCES	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
17	MECHANICAL STRENGTH	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
	VENTILATION	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
18	BULLET RESISTANCE	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
19	EXPLOSION RESISTANCE	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
20	RESISTANCE TO REPEATED OPENING & CLOSING	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
21	BEHAVIOUR BETWEEN DIFFERENT CLIMATES	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
22	BURGLAR RESISTANCE	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	
23	SPECIAL REQUIREMENTS	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	npd	

Notified Body test reports completed by British Board of Agrément and BSI

Name	Director	Signed	Date

CE DECLARATION FOR GLAZED WINDOWS & DOORS**PAGE 3 OF 3****COMPANY SUPPLYING GLAZED WINDOWS & DOORS:****Modplan Ltd., Imperial Building, Bridge Street, West End, Abercarn. United Kingdom. NP11 4SB****MANUFACTURER: Modplan Ltd., Imperial Building, Bridge Street, West End, Abercarn. United Kingdom. NP11 4SB**

History amendments

Summary amendment	Issue	Authorised by	Position	Date
First issued	1	DL Jones	QA Manager	01/02/2010
Update for Constructions Product Regulation July 2013	2	DL Jones	QA Manager	05/04/2013